

PRUSIK LINES Ropes & Accessories

5/16" Dia. Technora

6,200 lb. tensile strength. Very high heat and abrasion resistance. A high performance Technora cover over Polyester core. Technora aramid fiber decomposes at 500° Centigrade. (932° F)



Part No.: 1S-10T-06S Dia: 5/16" Color: Natural (Gold)

SPECIFICATIONS:

Construction: Braided Polyester cover/Parallel Nylon core
Avg. Tensile Strength: 6,200 lbs.
Avg. lbs. per 100 ft.: 2.7 lbs.
Standard Pkg: 600 ft. spool



1/4" and 5/16" Dia. Composite Braid

Constructed of 16-strand braided composite Polyester over Nylon parallel core. This rope features excellent holding power when tying Prusik knots.



Colors Available

Blue • Yellow • Red
White • Black

Part Number	DIA.	Tensile Strength Avg. Lbs.	Aprx. Weight (lbs. per 100 ft.)	Color	Std. Spool
1S-08	1/4"	2,700	2.2	Specify	600 ft
1S-10	5/16"	4,200	9.5	Specify	600 ft

BULL ROPES (Urethane Coated) Ropes & Accessories

Premium Double Braid Composite Fiber

Double-braid/composite construction of Polyester cover over Nylon core for higher tensile strength and better shock load performance. Urethane coated for abrasion resistance.



Part Number	DIA.	Tensile Strength Avg. Lbs.	Aprx. Weight (lbs. per 100 ft.)	Urethane Color	Std. Spool	Std. Hank
4BR-16C3-06S	1/2"	10,050	7.6	Green	600 ft	150 ft.
4BR-18C1-06S	9/16"	12,285	9.5	Blue	600 ft	150 ft.
4BR-20C5-06S	5/8"	15,320	12.0	Orange	600 ft	150 ft.
4BR-24CY-06S	3/4"	25,730	16.7	Yellow	600 ft	150 ft.



U.S. Rigging Supply • 888-260-7444
FAX: 714.545.3311 • www.usrigging.com

Pelican Rope Works • 888-860-7673
FAX: 714.545.7673 • www.pelicanrope.com

